


MSR-2Y(St)Y Pimf - Timf

1/1

PE insulated, individual & overall screened, unarmored, PVC sheathed instrumentation cable

Construction



1. Conductor: bare annealed copper, stranded, cl. 2 acc. IEC 60228
2. Insulation: PE
3. Cabling elements: pairs or triples
 colour identification: pairs: BLACK/WHITE, each core numbered
 triples: BLACK/WHITE/RED, each core numbered
4. Individual screening: laminated Alu/PET tape (9µm Alu/12µm PET) in contact with a tinned copper drain wire 0,5 mm² (7x0,30 mm)
 Cabling elements assembled in concentric layers
5. Overall screening: laminated Alu/PET tape (9 µm Alu/12 µm PET) in contact with a tinned copper drain wire 0,5 mm² (7x0,30 mm)
6. Outer sheath: flame-retardant PVC
 Outer sheath color: black or blue or according to customer specification
 Outer sheath marking: EUPEN MSR-2Y(St)Y Pimf 4x2x1,0 mm² 300V
 + year + meter-marking
 or according to customer specification

Electrical Properties acc. to EN 50288-7 (valid for single- and multi pair/triple types)

Voltage rating (V)	300 V				500 V				
	0,5	0,75	1,0	1,5	0,75	1,0	1,5	2,5	
Conductor cross-section (mm ²)	≤36,7	≤25,0	≤18,5	≤12,3	≤25,0	≤18,5	≤12,3	≤7,56	
Conductor resistance @ 20 °C (Ω/km)	≤115	≤115	≤115	≤115	≤115	≤115	≤115	≤115	
Mutual capacitance * (nF/km)	<25	<25	<25	<40	<25	<25	<40	<60	
L/R ratio * (µH/Ω)									
Test voltage core/core (V _{ac})		1000				2000			
Test voltage core/screen (V _{ac})		1000				2000			
Insulation resistance @ 20 °C (MΩ*km)		>5000				>5000			

* valid for pair cables

Laying conditions

Operating temperature	-30 °C to +70 °C
Laying temperature	-5 °C to +50 °C
Min. bending radius	7,5 x outer diameter
Oil resistance	ICEA S-82-552

Fire behaviour

Fire propagation	IEC 60332-1 (IEC 60332-3 Cat. A or Cat.C on request)
------------------	--

Application

Transmission of analog and digital signals for indoor and outdoor applications